

Tenveo NV-W series FHD PTZ Camera

NV5.8G Wireless Connection PTZ Camera

3X/10X/20X optical zoom for option



5.8G
Wireless Dongle

USB3.0

WIDE
View Angle

WIDE
Compatibility

Tenveo NV-W series cameras, equipped with a 1/2.8" SONY CMOS sensor with 2.38 megapixels, can deliver high-definition 1080p@60fps videos with a wide field of view. We have 3X/10X/20X Optical zoom for you to choose. Enjoy precise high-speed PTZ movement and experience latest 5.8G wireless connection technology with NV-W series cameras.

3X/10X/20X Optical Zoom 1080P HD Video Camera

3X/10X/20X optical zoom for your option, easy to meet the needs of small to large-sized conference rooms. Zoom in to examine the details, the image is as seen by eyes without distortion.



Wide Compatibility

Compatible with Zoom, Skype for business, Microsoft Lync(Teams), VooV Meeting, CISCO WebEx and other conferencing software. System Requirements: Windows 7, Windows 8.1, Windows 10, Windows 11, Android, Mac OS™ 10.10 or higher, Linux (Required to support UVC).



Accurate, Smooth and Silent PTZ Movements

Adopting high accurate video motor mechanism, these cameras work silently and efficiently to the presets position with the angle of 350° horizontally ($\pm 175^\circ$) and 180° vertically ($\pm 90^\circ$). They also support preset position settings up to 64.



Tilt: -90° - $+90^\circ$

Pan: -175° - $+175^\circ$

Model No.	NV3W	NV10W	NV20W
Sensor	1/2.8"SONY CMOS		
Effective Pixels	2.38 mega pixel		
Video Signals	1080p@60/50/30/25fps, 720p@60/50/30/25fps		
Zoom	3x optical zoom	10x optical zoom	20x optical zoom
Lens	f=2.38-7mm	f=5.76-46.09mm	f=5.9-94.4mm
Aperture	F1.96-3.64	F1.8-2.6	F1.8-3.9
Horizontal Angle	103.69°(W)-42.12°(T)	54.7°(W)-6.8°(T)	52.1°(W)-3.4°(T)
Vertical Angle	67.14°(W)-24.87°(T)	30.8°(W)-3.8°(T)	29.3°(W)-1.9°(T)
Diagonal Angle	113.91°(W)-47.55°(T)	62.8°(W)-7.8°(T)	59.8°(W)-3.9°(T)
Video Output	USB 3.0 / 5.8G Wifi		
Video Encoding Format	H.264, H.265, MJPG, YUY2		
Video Resolution	1080P (1920 *1080) etc		
Signal Standard	NTSC/PAL		
Preset Position	User can set up to 255 presets (10 presets by IR remote)		
Control Interface	RS-232 (input only), RS-485, USB		
Wifi	Frequency band: 5G/Distance: 10 meters		
Shutter	1/30s-1/10000s, auto		
Baud Rate	2400/4800/9600/38400bps		
Control Protocol	VISCA, PELCO-D, PELCO-P(RS-232, RS-485)		
USB Protocol	UVC1.1		
Minimal Illumination	0.1Lux		
SNR	≥50dB		
Horizontal Rotation	350° (±175°) 0.1°/s ~ 100°/s		
Vertical Rotation	180° (±90°)0.1°/s ~ 80°/s		
Power Supply	DC 12V/2A		
Power Consumption	12W		
Work Temperature	0°~+50°		
Work Humidity	0~95% RH		
Product Size	181*184*174mm/285*217*197mm(before / after packing)		
Product Weight	1.5kg/2.0kg (net / gross weight)		

For NV series cameras, we have multiple options with USB, HDMI, SDI, RJ45 and POE Ethernet outputs. The updated version with wireless 5.8G wifi connection can meet various requirements.

Hotline : 400-1080-686
Tel : 0086-755-8526-1373
Email : sales01@tenveo.com
Address : A-1st Floor, B-8th Floor, Fukang Keji Mansion, Yousong Road,
Fukang Community, Longhua Dist., ShenZhen, China

